

# Storage Tank (500BBL)

## SPECIFICATION SHEET

ARC Well Equipment's 500BBL Storage Tanks are specifically designed for produced water during well completions or servicing. They are easy to rig up, have multiple connection points, and are the industry leader for ease of cleaning and safety due to the open top design and large access manway.

Storage Tanks are provided on a rental basis.



### OVERALL DIMENSIONS

Overall dimensions	13.7m x 2.5m x 4.3m (LxWxH)
Total tank capacity	79.5kL (500 BBL)
Aggregate trailer mass	15.1 tonne
Load over kingpin	6.5 tonne

*Weights and dimensions can vary depending on options. Please contact ARC for specific information.*

### OPERATIONS

- Rockover design, road-trainable, no permits required
- Full-size submarine access door into tank
- Ladder accessible viewing platform to observe inflows and fluid heights
- Sight glass fluid level indicator
- Sunken suction sump with strainer grate

### PUMP AND PLUMBING

- 2 x 4" female camlock rear fill points  
TEXT
- (into sand trap when fitted)
- 2 x 4" male camlock low level suction points at front
- 1 x 4" male camlock high level suction

### FEATURES

- Rugged 200x100 RHS perimeter frame
- 6mm crimped walls, 10mm floors
- Tandem axle, leaf spring suspension
- Internal surfaces coated with 400µm corrosion resistant paint

### OPTIONS

- 5kL sand trap (at rear)
- Hoses to suit customer needs
- Diesel-powered or electric transfer pumps available for mounting to front deck
- Radar fluid level monitoring
- High level overflow warning siren

*All ARC supplied products are RPEQ certified and are supplied with operator manuals*